

Technical data

Type:

acc. to DIN 19569-4
four-sided sealing

Nominal diameter:

Installation:

Manhole adapter for round manhole

Fixing:

Wall fixing Clamp mounting

Option:

Sealing collar

Installation depth:

mm (invert to top of square cap)

Max. pressure:

6.0 mWC

Pressure side:

on- and off-seating

Operation

Drive:

Square cap above wall, key operated
with free-standing rod

Material

Plate / frame:

Stainless steel □ SS304 / □ SS316L

Seal:

EPDM

Wedges:

Plastic PA

Stem nut:

Bronze

Stem:

Stainless steel SS316L

Supply includes

Stem extension

Anchor rods with mortar capsules

Sealant (290 ml cartridge)

Note

Required where the structure
wall ends early.

Project-specific data

Client

Project

Structure

Item

Remarks

Quantity

Prepared by

Date

Contact

TESACO-TECHNIQUE GmbH

Tel. +49 6430 611030

info@tesaco.de

www.tesaco.de


It's this easy

1. Complete technical
data

2. Add project data

3. Save PDF

4. Send to **TESACO**



Drawing no.:	PZ-R-M-003	Issue date:	27.06.2026	Revision: -	Sheet: 1 / 1
Note: This planning drawing shows the standard design and is intended as a planning reference.					